



**RAJASTHAN TRANSMISSION CORPORATION (RTPCL)**  
**JYA VIDYUT PRASARAN NIGAM LTD**

(AN ISO 9001:2000 Certified Company)

**OFFICE OF THE EXECUTIVE ENGINEER (220 KV GSS) DHOD**

NO./RVPN/EE/GSS/DHOD/ESTT./F str.painting / D 324 DATE:14.12.2016

To

All Registered Contractors  
Under T&C, Ajmer Zone

Sub:- Consent for painting work of Structures , Transformers and other associated  
equipment at 220 KV GSS, RVPN,Dhod.

Ref:- 1. CLRC Order No. RVPN/SE/SSPC/TK/A.1/TN2975/CLRC/D.501  
DT24.05.2013.  
2. RVPN/SE(SSPC)/XEN(TK)/A.1/D 1317 DT 12/10/2015.

Dear sirs ,

With reference to the above and being registered contractor of Ajmer Zone  
for work on CLRC, it is to inform you that this office proposed to award contract  
for painting work of Structures, transformers & associated equipments at 220 KV  
GSS, RVPN, Dhod , the details of work is mentioned in the enclosed G-Schedule.

Therefore , convey your consent within 10 days in writing along  
with copy of valid registration so the case may be further processed.

Encl: -GøSchedule .



Executive Engineer  
220 KV GSS RVPN DHOD

No.	Description of Work	Unit	Quantity	Rate	Amount
1.	<b>Painting of structures:</b>				
2.2	<b>Painting of old painted steel structures:-</b> Alluminium painting of old painted steel Structures at 220KV GSS,Dhod, including Paint & painting brush, emery paper, cloth & solvent etc.The surface shall be first rubbed With wire brush / emery paper and there after Wiped with cloth to remove rust and dust or Any other deposit on erected M.S.steel structures.Two coats of alluminium paint shall be applied. Each subsequent coat shall be applied only after the previous has dried up. The paint used shall be from any of the following recognized manufacturers,namely Asian /Nerolac /Berger /Johnson Nicholson	Sq. Meters	2100 (Approx)	24=00	50400=00
2.3	<b>Painting of Transformer &amp; Equipments:-</b> Enamel painting of power Transformer and other equipment including supply of paint and spray painting set, emery paper, cloth and solvent etc.at GSS by cleaning surface thoroughly with soda/ caustic solution to clean oily surface and thereafter washing with water. Thereafter, two coats of smoke gray synthetic enamel paint shall be applied by spray method. Each subsequent coat shall be applied after the previous coat has fully dried up. The paints used shall be from any of the following recognized manufacturers namely Assian/Nerolac/Berger/Johnson Nicholson. In the case of surface area of radiators,those fins will only be considered which are actually feasible and approachable for painting by spray or brush.	Sq. Meters	700 ( Approx)	25=00	17500=00
	Total Cost				67900=00
	60% above				40740=00
	G.Total ( Rs One lac Eight thousand six hundred forty only)				108640=0



Executive Engineer  
220 KV GSS RVPN DHOD



**PDF**  
Complete

*Your complimentary  
use period has ended.  
Thank you for using  
PDF Complete.*

[Click Here to upgrade to  
Unlimited Pages and Expanded Features](#)