



RAJASTHAN RAJYA VIDYUT PRASARAN NIGAM LTD.

(Regd. Office: Vidyut Bhavan, Jyoti Nagar, Janpath, Jaipur)

(AN ISO-9001-2008 CERTIFIED COMPANY)

OFFICE OF THE ASSISTANT ENGINEER (132 kV GSS)

RVPN, MANDORE, JODHPUR

No. RVPN / EN/ 132 KV / GSS / Mandore /S. Purchase / F. / D. 99 Dt. 29 ⁰⁹/₁₇

To,

All registered contractor of
T&C RVPN, Jodhpur Zone,

Subject:- Painting work of Power Transformer, GSS Equipments and Structures at
132 kV GSS RVPN, Mandore at CLRC rate for financial year 2017-18.

On the above cited subject it is bring to your kind notice that Power Transformer, GSS Equipments and Structure Painting work are required to be carried out at 132 kV GSS RVPN, Mandore on CLRC rate (as per "G" schedule enclosed) and other terms & conditions of CLRC rate contract as approved by RVPN.

If you are interested for carrying out this work on CLRC rate, please send your consent/acceptance within 10 days from the date of dispatch of this letter.

Encl:- "G" Schedule.


Assistant Engineer
132 kV GSS RVPN, Mandore

RAJASTHAN RAJYA VIDYUT PRASARAN NIGAM LIMITED

G Schedule for painting of 132/33 kV Transformers (2 Nos.), other equipments & steel structures installed at 132 kV GSS Mandore

(As per BSR for Repair & Maintenance work of EHV Lines & GSS applicable from 01.01.2011)

Code No.	Description	Unit	Rate (Rs.)	Qty.	Amount (Rs.)	Remarks
2.1	PAINTING OF UNPAINTED STEEL STRUCTURES:					
	Aluminium painting of unpainted steel structures at the GSS including paint and painting brush, emery paper, cloth & solvents etc. The surface shall be first cleaned with wire brush/emery paper and thereafter wiped with cloth to remove rust and dust or any other deposits on erected M.S. steel structures & beams. One coat of red oxide paint shall be applied after carrying out cleaning and allowed to dry. Thereafter, two coats of aluminum paint shall be applied. Each subsequent coat shall be applied only after the previous coat has dried up. The paint used shall be from any of the following recognized manufactureres, namely Asian/Nerolac/Berger/Johnson Nicholson.	SQ.Metre	31	60	1860.00	
2.2	PAINTING OF OLD PAINTED STEEL STRUCTURES:					
	Aluminium painting of old painted steel structures at the GSS including supply of paint and painting brush, emery paper, cloth & solvents etc. The surface shall be first cleaned with wire brush/emery paper and thereafter wiped with cloth to remove rust and dust or any other deposits on erected M.S. steel structures. Two coats of aluminum paint shall be applied. applied. Each subsequent coat shall be applied only after the previous coat has dried up. The paints used shall be from any of the following recognized manufactureres, namely Asian/Nerolac/Berger/Johnson Nicholson.	SQ.Metre	24	100	2400.00	
2.3	PAINTING OF TRANSFORMERS & EQUIPMENTS:					
	Enamel painting on power transformers & other equipments including supply of paint & spray painting set, emery paper, cloth & solvents, etc. at GSS by cleaning surface thoroughly with soda/washing with water. Thereafter, two coats of smoke gray synthetic enamel paint shall be applied by spray method. Each subsequent coat shall be applied after the previous coat has fully dried up. The paints used shall be from any of the following reconized manufacturers, namely Asian/Nerolac/Berger/John Nicholson. In case of surface area of radiators, those fins will only be considered which are actually leasible and approachable for painting by spray or by brush.	SQ.Metre	25	1000	25000.00	
	TOTAL				29260.00	
	Add Premium @ 60%				17556.00	
	G. TOTAL				46816.00	



Assistant Engineer (132 kV GSS)
RVPNL, Mandore